

Leica DISTO™ D2

Technical Data	Leica DISTO™ D2
Typical Measuring Accuracy	± .06 inches
Range	0.16 ft - 197 ft
Distance in feet Diameter of Laser Dot in inches	33 ft, 167ft, 328 ft 0.2", 1.8", 2.36"
Minimum/Maximum Measurements	Yes
Continuous Measurements	Yes
Addition/Subtraction	Yes
Area/Volume Measurements	Yes
Pythagoras Calculation	Yes
Tilt Sensor display units	±45°, 0.00%
Recall Last Values	10
Time Delay Release	Yes
Display illumination	Yes
Measuring Units	0.000 m, 0.00 ft, 0' 00" 1/16, 0 1/16 in
Measurements Per set of Batteries	Up to 5,000
Multi-functional End Piece	Manual
Batteries	Typically AAA 2 x 1.5v
Spray proof/dust protected IP 54	Yes
Dimensions	4.37"x1.65"x0.91"
Weight with batteries	3.17 oz



Warranty 24 months as of the date of purchase.
Extended warranty 36 months on instrument
after being registered with Leica Geosystems
within eight (8) weeks of purchase.

All illustration, descriptions, technical specifications and prices are subject to change without notice.

JMA is a trademark of JMA Technology.
All Trademarks, Trade Names or logos are property of their respective owners.
Disto_D2_Specification_Version_1_00_00_20080419.ppp



TECHNOLOGY, INC.

6210 Skyline Drive
Houston, Texas 77057

Tel: 713-780-7262 Fax: 713-780-3010
<http://www.jmatech.com>

Copyrighted © 2008 JMA Technology, Inc.
4/19/08