

# Leica DISTO™ D3

Technical Data	Leica DISTO™ D3
Typical Measuring Accuracy	± .06 inches
Range	0.16 ft - 328 ft
Power Range Technology™	Yes
Distance in feet Diameter of Laser Dot in inches	33 ft, 167ft, 328 ft 0.2", 1.8", 2.36"
Minimum/Maximum Measurements	Yes
Continuous Measurements	Yes
Addition/Subtraction	Yes
Area/Volume Measurements	Yes
Room Calculation	Yes
Pythagoras Calculation	Yes
Tilt Sensor Horizontal Dist.	Yes
Tilt Sensor	
Measuring Range	±45°
Accuracy to Laser Beam	±0.3°
Accuracy to Housing	±0.3°
Tilt Sensor display units	±45°, 0.00%
Recall Last Values	20
Time Delay Release	Yes
Display illumination	Yes
Measuring Units	0.000 m, 0.00 m, 0.00 ft, 0' 00" 1/32, 0' 00" 1/16", 0' 00" 1/8", 0.0 in, 0 1/32 in, 0 1/16 in, 0 1/8 in
Measurements Per set of Batteries	Up to 5,000
Multi-functional End Piece	Automatic
Batteries	Typically AAA 2 x 1.5v
Spray proof/dust protected IP 54	Yes
Dimensions	4.29"x1.77"x0.94"
Weight with batteries	3.88 oz



Warranty 24 months as of the date of purchase.  
Extended warranty 36 months on instrument  
after being registered with Leica Geosystems  
within eight (8) weeks of purchase.

All illustration, descriptions, technical specifications and prices are subject to change without notice.

JMA is a trademark of JMA Technology.  
All Trademarks, Trade Names or logos are property of their respective owners.  
Disto\_D3\_Specification\_Version\_1\_00\_00\_20080419.ppp



**TECHNOLOGY, INC.**

6210 Skyline Drive  
Houston, Texas 77057

Tel: 713-780-7262 Fax: 713-780-3010  
<http://www.jmatech.com>

Copyrighted © 2008 JMA Technology, Inc.  
4/19/08