

# Leica DISTO™ D8

Technical Data	Leica DISTO™ D8
Typical Measuring Accuracy	± .04 inches
Range	0.16 ft - 666 ft
Power Range Technology™	Yes
Distance in feet Diameter of Laser Dot in inches	33 ft, 167ft, 328 ft 0.2", 1.8", 2.36"
Minimum/Maximum Measurements	Yes
Continuous Measurements	Yes
Addition/Subtraction	Yes
Area/Volume Measurements	Yes
Room Calculation	Yes
Pythagoras Calculation	Yes
Tilt Sensor Horizontal Dist.	Yes
Title Sensor Measuring Range	360°
Accuracy to Laser Beam	±0.1°
Accuracy to Housing	±0.1°
Tilt Sensor display units	0.0°, 0.00%, mm/m, in/ft
4 Folder Digital Viewfinder	Yes
Store Constant Value	1
Recall Last Values	30
Time Delay Release	Yes
Display illumination	Yes
Measuring Units	14 display modes for meters, feet, inches, yards
Measurements Per set of Batteries	Up to 5,000
Multi-functional End Piece	Automatic
Tripod Thread	Yes 1/4"-20 thread
Batteries	Typically AA 2 x 1.5v
Spray proof/dust protected IP 54	Yes
Dimensions	5.65"x2.12"x1.18"
Weight with batteries	6.88 oz



Warranty 24 months as of the date of purchase.  
Extended warranty 36 months on instrument after being registered with Leica Geosystems within eight (8) weeks of purchase.

All illustration, descriptions, technical specifications and prices are subject to change without notice.

JMA is a trademark of JMA Technology.

All Trademarks, Trade Names or logos are property of their respective owners.

Disto\_D8\_Specification\_Version\_1\_00\_00\_20090424.ppp



**TECHNOLOGY, INC.**

6210 Skyline Drive  
Houston, Texas 77057

Tel: 713-780-7262 Fax: 713-780-3010  
<http://www.jmatech.com>

Copyrighted © 2008 JMA Technology, Inc.  
4/24/09