

Leica DISTO™ D2

The small partner - for interior applications.



Measuring distances and calculating results with the smallest laser distance meter in world - Leica DISTO™ D2.


The compact and handy base model was specifically designed for indoor applications. Shortcut keys for addition, subtraction, area and volume calculation make measuring fast and very reliable. The last ten (10) measurements are also stored. As will all Leica Laser distance meters, the laser dot is clearly visible. You can always see your targeting point, even if the target object is in a hard to access area.

The Leica DISTO™ D2 - you will never use a measuring tape or wheel again!



Measure from edges and corners

With the flip-out end-piece you are equipped for any measuring situation.



Small and handy

Thanks to its ergonomic and compact design with soft grip, the Leica DISTO™ D2 sits securely in your hand and fits into any pocket.



Simply clever

Minimum and maximum measurements, tracking and storage of results makes your work much easier.

Features

- Measuring Range of .16' to 196' (± 0.06 in)
- Shortcut keys
- Illuminated 3-line display
- Flip-out End Piece
- Stake out function
- Time Delay release
- Simple Pythagorean functions
- IP 54

Your Advantages

- Precise, fast and reliable indoor distance measurements.
- Easy to use and rapid access to frequently used functions
- Measured values can be read even in the dark
- Measure from edges and corners.
- Set out equal distances.
- Measure without shake
- Indirect height and width measurements for inaccessible locations
- Splash and dust proof

What comes in the Box:

Leica DISTO™ D2, Holster, Hand Loop, Batteries (2 AAA 1.5v), Manual, safety Instructions.

All illustration, descriptions, technical specifications and prices are subject to change without notice.

JMA is a trademark of JMA Technology.

All Trademarks, Trade Names or logos are property of their respective owners.

Disto_D2_Literature_Version_1_00_00_20080419.ppp



TECHNOLOGY, INC.

6210 Skyline Drive
Houston, Texas 77057

Tel: 713-780-7262 Fax: 713-780-3010
<http://www.jmatech.com>

Copyrighted © 2008 JMA Technology, Inc.
4/19/08

Technical Data	Leica DISTO™ D2
Typical Measuring Accuracy	± .06 inches
Range	0.16 ft - 197 ft
Distance in feet Diameter of Laser Dot in inches	33 ft, 167ft, 328 ft 0.2", 1.8", 2.36"
Minimum/Maximum Measurements	Yes
Continuous Measurements	Yes
Addition/Subtraction	Yes
Area/Volume Measurements	Yes
Pythagoras Calculation	Yes
Recall Last Values	10
Time Delay Release	Yes
Display illumination	Yes
Measuring Units	0.000 m, 0.00 ft, 0' 00" 1/16, 0 1/16 in
Measurements Per set of Batteries	Up to 5,000
Multi-functional End Piece Batteries	Manual Typically AAA 2 x 1.5v
Spray proof/dust protected IP 54	Yes
Dimensions	4.37"x1.65"x0.91"
Weight with batteries	3.17 oz

Warranty 24 months as of the date of purchase. Extended warranty 36 months on instrument after being registered with Leica Geosystems within eight (8) weeks of